

RUEDAS VITRIFICADAS TIPO 1



RUEDAS GRISES PARA ESMERILAR



HIERRO GRIS.

CLAVE	DIMENSIONES	ESPECIFICACIONES	MAX RPM.
10	76X13X12.7	3A60N5V	9420
110	150X13X25.4	3A36Q5V	4710
120	150X13X25.4	3A60N5V	4710
140	150X20X25.4	3A24Q5V	4710
150	150X20X25.4	3A36Q5V	4710
160	150X20X25.4	3A46O5V	4710
170	150X20X25.4	3A60N5V	4710
180	150X20X25.4	3A80M5V	4710
200	150X25X25.4	3A24Q5V	4710
210	150X25X25.4	3A36Q5V	4710
220	150X25X25.4	3A46O5V	4710
230	150X25X25.4	3A60N5V	4710
240	150X25X25.4	3A80M5V	4710
250	150X25X25.4	3A100M5V	4710
260	175X13X31.7	3A60N5V	4035

300	175X20X25.4	3A80M5V	4035
310	175X25X25.4	3A24Q5V	4035
320	175X25X25.4	3A36P5V	4035
330	175X25X25.4	3A46O5V	4035
340	175X25X25.4	3A60N5V	4035
370	200X20X25.4	3A60N5V	3530
380	200X25X25.4	3A24Q5V	3530
390	200X25X25.4	3A36Q5V	3530
400	200X25X25.4	3A46O5V	3530
410	200X25X25.4	3A60N5V	3530
420	200X25X25.4	3A80M5V	3530